

LABDex



Hot Air Block Incubator LX222HAB

Email: info@labdex.com **website:** www.labdex.com

Description

Hot Air Block Incubator LX222HAB is a microprocessor-controlled multipurpose incubator with PID control. Equipped with simultaneous incubation function for improved results efficiency.

Specifications

Fan speed range	1200 ~ 3200 rpm
Incubation space size (W x D x H)	245 × 215 × 85 mm
Temperature display accuracy	0.1 °C
Time range	1 min ~ 99 h 59 mins
Temperature control range	RT 5 °C ~ 60 °C
Temperature setting range	5 °C ~ 60 °C
Temperature stability at 37 °C	± 0.2 °C
Temperature uniformity	≤ ± 0.5 °C
Voltage	AC 220 V / AC 110 V, 50 / 60 Hz
Power	300 W
Fuse	250 V, 2A / 4A, Φ5 x 20
Dimension	275 × 395 × 150 mm
Weight	8.1 kg

Features

- ˆ LED display, microprocessor controls temperature and time
- ˆ Various sample containers are available (such as micro-plate, reagent cards frame, beaker, culture dish, etc,) which can be put into the incubation space
- ˆ Transparent lid for easy experiment visualization
- ˆ Beeping alarm at the end of every cycle
- ˆ Simultaneous incubation of samples for improved efficiency

Applications

- ˆ Used for sample incubating in micro-plates, Gel cards, beakers, culture dishes, etc.

Optional Accessories

Accessory No	Specifications
01	Stands for plates (2 Standard plates)
02	Stands for gel cards (12 x 2 Blood type reagent card)



71-75 Shelton Street Covent Garden, London WC2H 9JQ UK.
Email: info@labdex.com | Website: www.labdex.com